

# JSHint

```
$ sudo npm install jshint -g
```

## .jshintrc

```
{
  "undef": true,
  "unused": true,
}
```

JSON

```
$ jshint [ ]
```

## (Enforcing)

<b>bitwise</b>	<code>^(XOR),        bit</code>
<b>camelcase</b>	<code>test      var Test      (      UPPER_CASE)      (      var</code>
<b>curly</b>	<code>if      while      ({} )</code>
<b>eqeqeq</b>	<code>==      !=      ===      !==</code>
<b>es3</b>	<code>es3</code>
<b>forin</b>	<code>for-in      for (var key in obj)      if</code>
	<code>(obj.hasOwnProperty(key)) {}      hasOwnProperty      .)      가      . (</code>
<b>freeze</b>	<code>Array, Date, String      Array.prototype.count = function() { };</code>
<b>immed</b>	<code>var a = function() {}();      가</code>
<b>indent</b>	

<b>latedef</b>				hoisting
<b>newcap</b>	new new Animal();			. new animal();
<b>noarg</b>	가	arguments.caller	arguments.callee	
<b>noempty</b>	for (var i=0;i < 10;i++) { }	for		
<b>nonew</b>	new Animal();			
<b>plusplus</b>	+, -			
<b>quotmark</b>			true 가 single	double
<b>undef</b>		가		
<b>unused</b>		가		
<b>strict</b>	ECMAScript 5 strict mode	strict mode		
<b>trailing</b>		가	가	가
<b>maxparams</b>				
<b>maxdepth</b>				
<b>maxstatements</b>				
<b>maxcomplexity</b>		(cyclomatic complexity)		
<b>maxlen</b>				

## (Relaxing)

<b>asi</b>				
<b>boss</b>	if (a = 1)			
<b>debug</b>	debugger;			
<b>eqnull</b>	== null			
<b>esnext</b>	ECMAScript 6			
<b>evil</b>	eval			
<b>expr</b>	true.should.be.ok;			
<b>funcscope</b>	if (true) { var a = 1; } 가			,
<b>globalstrict</b>	ECMAScript 5 strict mode	strict mode		
<b>iterator</b>	iterator			
<b>lastsemic</b>				
<b>laxbreak</b>			laxcomma	
<b>laxcomma</b>		(	)	
<b>loopfunc</b>				

<b>moz</b>	(JavaScript 1.7)		
<b>multistr</b>	\		
<b>notypeof</b>	typeof	typeof	
<b>proto</b>	<u>proto</u>		
<b>scripturl</b>	<a href="javascript:>		URL(javascript:)
<b>smarttabs</b>			
<b>shadow</b>		variable shadowing	
<b>sub</b>	obj['key']		
<b>supernew</b>	new function () {}	new Object;	가
<b>validthis</b>	strict	가	this

## JSHint가

<b>browser</b>	document, navigator	console, alert
<b>couch</b>	CouchDB	
<b>devel</b>	console, alert	/
<b>dojo</b>	Dojo	
<b>jquery</b>	jQuery	
<b>mootools</b>	MooTools	
<b>node</b>	Node.js	Node.js
<b>nonstandard</b>	escape unescape	,
<b>phantom</b>	PhantomJS	
<b>prototypejs</b>	Prototype	
<b>rhino</b>	Rhino	
<b>worker</b>	Web Worker	
<b>wsh</b>	Windows ScriptHost	
<b>yui</b>	YUI	

## Deprecated

<b>nomen</b>		(_)	가
<b>onevar</b>	var	.	.
<b>passfail</b>		.	.
<b>white</b>	JSHint가	(Douglas Crockford)	가

- [JSHint](#)
- [JSHint Options](#)
- [JSHint](#)

From:

<http://www.obg.co.kr/doku/> - **OBG WiKi**



Permanent link:

<http://www.obg.co.kr/doku/doku.php?id=programming:javascript:jshint>

Last update: **2020/11/29 14:09**